

IRWD - CLIIP Eligible Products List

Hydrometers & Master Valves

Hydropoint Flow3						
1-1/2 " Hydrometer (Flanged) Flow3						
2 " Hydrometer (Flanged) Flow3						
3 " Hydrometer (Flanged) Flow3						
4 " Hydrometer (Flanged) Flow3						
6 " Hydrometer (Flanged) Flow3						
1-1/2 " Hydrometer (Threaded)						
2 " Hydrometer (Threaded)						
MODEL + REGISTER TYPE	pulse per gallon	gallons per pulse	K	Offset	+ VALVE TYPE	
WTF3-150 1 1/2" MPT	RS	1	1	60.000	0.0	NO = Normally Open NC = Normally Closed
	PD	187.900	0.0053	0.319	0.0	
	PDFL					
WTF3-200 2" FPT	RS					
	PD	117.000	0.0085	0.510	0.0	
	PDFL					
WTF3-300 3" Flanged	RS	1	1	60.000	0.0	
	PD	48.710	0.0205	1.232	0.0	
	PDFL					
WTF3-400 4" Flanged	RS	1	1	60.000	0.0	
	PD	17.933	0.0566	3.335	0.0	
	PDFL					
WTF3-600 6" Flanged	PD	5.747	0.1741	10.437	0.0	
	PDFL					

RS = Reed Switch (*low frequency*) **PD** = Photo Diode (*high frequency*)
PDFL = Photo Diode (*high frequency*) and includes (1) FlowLink-XT

WTF3-200-PD-NO = 2" Normally Open Flow3 w/ Photo Diode Register
WTF3-150-RS-NC = 1 1/2" Normally Closed Flow3 w/ Reed Switch Register
WTF3-300-PDFL-NC = 3" Normally Closed Flow3 w/ Photo Diode Register and (1) FlowLink-XT

Baseline Model Hydrometer
1-1/2 " Hydrometer
2 " Hydrometer
3 " Hydrometer
4 " Hydrometer
BHM Series Hydrometer & Master Valve Combination
BL-BHM150 - 1.5" Two-Wire Ready Hydrometer, Normally Closed (NPT Male Threaded)
BL-BHM150-NO - 1.5" Two-Wire Ready Hydrometer, Normally Open (NPT Male Threaded)
BL-BHM200 - 2" Two-Wire Ready Hydrometer, Normally Closed (NPT Female Threaded)
BL-BHM200-NO - 2" Two-Wire Ready Hydrometer, Normally Open (NPT Female Threaded)
BL-BHM300 - 3" Two-Wire Ready Hydrometer, Normally Closed (Flanged)
BL-BHM300-NO - 3" Two-Wire Ready Hydrometer, Normally Open (Flanged)
BL-BHM400 - 4" Two-Wire Ready Hydrometer, Normally Closed (Flanged)
BL-BHM400-NO - 4" Two-Wire Ready Hydrometer, Normally Open (Flanged)

IRWD - CLIIP Eligible Products List

Netafim Hydrometer				
METER SIZE	REGISTER OUTPUT TYPE	PULSE PER GALLON	GALLONS PER PULSE	MODEL NUMBER (MANUAL ELECTRIC)
1 1/2"	RS	1	1	LHM15TG1-MEL
	PDH	187.900	0.0053	LHM15TG0053-MEL
	ER	10	0.1	LHM15EM11AAFME
2"	RS	1	1	LHM2TG1-MEL
	PDH	117.000	0.0085	LHM2TG0085-MEL
	ER	10	0.1	LHM2EM11AAFME
3"	RS	1	1	LHM3FG1-MEL
	PDH	48.710	0.0205	LHM3FG0205-MEL
	ER	10	0.1	LHM3EM11AAFME
4"	RS	1	1	LHM4FG1-MEL
	PDH	17.933	0.0566	LHM4FG0566-MEL
	ER	10	0.1	LHM4EM11AAFME
6"	RS	0.1	10	LHM6FG10-MEL
	PDH	5.747	0.1741	LHM6FG1739-MEL
	ER	1	1	LHM6EM11AAFME
8"	RS	0.1	10	LHM8FG10-MEL
	PDH	3.152	0.317	LHM8FG317-MEL
	ER	1	1	LHM8EM11AAFME

Netafim Hydrometers are standard in a manually closed configuration. To order a Normally Open (NO) configuration, call Netafim Customer Service at 1 (888) 638-2346 for ordering information.

Rain Bird - Master Valves
HV & HVF Series
DV/DVF Series
PEB/PESB Series
PESB-R Series
EFB-CP Series
300-BPES

TORO - Master Valves
TPV Series
250/260 Series
254/264 Series
252 Series
P-220 Series
220 Brass
P-220S Scrubber Series

IRWD - CLIIP Eligible Products List


Hunter - Master Valves
PGV Series
PGV-ASV Series
ICV Series
IBV Series

Buckner/Superior - Master Valves
3100 Series
3200 Series
3100PRS Series


GRISWOLD CONTROLS - Master Valves
2000 Series Heavy Duty Irrigation Valves

FlowLink & Other Connection Components


Hydropoint FlowLink



FlowLink - CT




FlowLink - FXT



FlowLink - EXT

Model #	FlowLink CT	FlowLink FXT	FlowLink EXT	Product Description
WTFL-XT	X	X		Provides Flow Sensor input and master valve control using a spare unused field wire
WTFL-XT+	X	X	X	Provides Flow Sensor input and master valve control via an existing station field wire

Hydropoint FlowShare



WTFS-SP - Enables more than one WeatherTRAK controller to share a single Flow Sensor and Master Valve

IRWD - CLIIP Eligible Products List

Creative Sensor Technology
PWY-400 Pathway Wire Sharing System
HO2 Pathway Wire Sharing System

Tucor, Inc.	
The Tucor Hybrid 3D	
Hybrid 3D	
Part Number	Product Description
3D-6	3D with 2 wire output for up to 6 valves, flow sensor, master valve, Nema 4X enclosure with flex conduit connection.
3D-6-ASSY	Preprogrammed assembly with 3D-6 with 3DSD-FMV combo decoder and 3DLD-050-1 transition decoder
3D-6-DL	3D with 2 Wire Output for up to 6 valves, flow sensor, master valve, NEMA 4x enclosure and flex conduit connection and factory installed DL-PCB
3D-24	3D with 2 Wire Output for up to 24 valves, flow sensor, master valve, NEMA 4x enclosure and flex conduit connection
3D-24-DL	3D with 2 Wire Output for up to 24 valves, flow sensor, master valve, NEMA 4x enclosure and flex conduit connection and factory installed DL-PCB
3D DECODERS	
3DLD-050	Single Valve Line Decoder for use with 3D. MUST PROGRAM
3D-FMV-M	Combination 3DSD-100-M and 3DLD050-MV For flow sensor and master valve
3DLD-050-MV	Preprogramed Single Valve Line Decoder for use with 3D 1 MV
3DLD-050-1	Preprogramed Single Valve Line Decoder for use with 3D 1 Brown
3DLD-050-2	Preprogramed Single Valve Line Decoder for use with 3D 2 Black
3DLD-050-3	Preprogramed Single Valve Line Decoder for use with 3D 3 Orange
3DLD-050-4	Preprogramed Single Valve Line Decoder for use with 3D 4 Red
3DLD-050-5	Preprogramed Single Valve Line Decoder for use with 3D 5 Violet
3DLD-050-6	Preprogramed Single Valve Line Decoder for use with 3D 6 Blue
3DSD -100	Flow Sensor Decoder for 3D
3DSD-100-M	Flow Sensor Decoder for 3D with 5 VDC for photo diode register. (Hydrometer)
3D WITH FLOW ASSEMBLY	
3D-6-FA -1	"Flow Assembly includes the 3D-6-ASSY, 1" flow sensor with plastic tee fitting Includes 3D-FMV-M Sensor/MV decoder"
3D-6-FA -1.5	"Flow Assembly includes the 3D-6-ASSY, 1.5" flow sensor with plastic tee fitting Includes 3D-FMV-M Sensor/MV decoder"
3D-6-FA -2	"Flow Assembly includes the 3D-6-ASSY, 2" flow sensor with plastic tee fitting Includes 3D-FMV-M Sensor/MV decoder"
3D WITH FLOW ASSEMBLY (HYDROMETER PDR)	
3D-6-HM-PDR-NO-1.5	Flow assembly includes the 3D-6-ASSY, 1.5" Hydrometer with high frequency photo diode / N.O. master valve valves Includes 3D-FMV-M Sensor/MV decoder
3D-6-HM-PDR-NO-2	Flow assembly includes the 3D-6-ASSY, 2" Hydrometer with high frequency photo diode / N.O. master valve valves Includes 3D-FMV-M Sensor/MV decoder
3D-6-HM-PDR-NO-3	Flow assembly includes the 3D-6-ASSY, 3" Hydrometer with high frequency photo diode / N.O. master valve valves Includes 3D-FMV-M Sensor/MV decoder
3D-6-HM-PDR-NO-4	Flow assembly includes the 3D-6-ASSY, 4" Hydrometer with high frequency photo diode / N.O. master valve valves Includes 3D-FMV-M Sensor/MV decoder
3D COMPONENTS	
3D-DL-PCB	Add on for PCB Board with Dynamic Load Feature for ETWater, WeatherTrak and Rain Master Controllers to buffer line voltage monitoring

Flow Sensors

TORO
TFS Flow Sensors

Badge Meter
Impeller - Series 228PV PVC Tee Industrial Flow Sensors
Impeller - Metallic Tee Type Flow Sensors - Series 250

IRWD - CLIIP Eligible Products List

Rain Bird	
Brass Tees	
FS200B	
FS150B	
FS100B	
Plastic Tees	
FS400P	
FS300P	
FS200P	
FS150P	
FS100P	

Creative Sensor Technology	
FSI T Series PVC Flow Sensor	
FSI B Series Brass Flow Sensor	

Pressure Regulating Valves

Watts & Wilkins-Zurn	
	Model #
Watts - 3/4" Pressure Reducing Valve	*
Watts - 1" Pressure Reducing Valve	*
Watts - 1 - 1/2" Pressure Reducing Valve	*
Watts - 2" Pressure Reducing Valve	*
Wilkins-Zurn - 3/4" Pressure Reducing Valve	*
Wilkins-Zurn - 1" Pressure Reducing Valve	*
Wilkins-Zurn - 1 - 1/4" Pressure Reducing Valve	*
Wilkins-Zurn - 1 - 1/2" Pressure Reducing Valve	*
Wilkins-Zurn - 2" Pressure Reducing Valve	*

* IRWD will make final determination on product eligibility for program for various makes and models not found on list.